

Commercial Lighting

Recessed Mounted

Tulip Spot light



A high-performance recessed anti-glare downlight designed for premium architectural and interior applications. This fixture combines a sleek, minimalist aesthetic with advanced thermal management, making it an ideal choice for engineers and lighting designers seeking both durability and visual comfort.

Physical & Material Specs

Housing Material: Die-cast Aluminum Heat Sink

Diffuser Type: Polycarbonate

IP Rating: IP20

Dimensions: Ø 70mm, H100mm

Finish Colors: Sanded Black, Pearl White, Optional

Reflector: Black or White



Electrical Parameters

Input Voltage: AC 220-240V, 50/60Hz

Power Factor (PF): PF > 0.9

Driver Brand: Lifud, Philips

LED Brand: Bridgelux, Philips

Photometric Data

Luminous Efficacy: >100 lm/W

Color Temperature (CCT): 3000K, 4000K, 6500K

Color Rendering Index (CRI): Ra > 80

Beam Angle: 15°-24°

Code	Wattage	Lumen	CRI	Beam Angle	CCT	LED	Driver	Dim.
LTS-SP7010840	10	960L	>80	15°-24°	4000K	Philips Bridgelux	Philips Lifud	Ø70*100 mm
LTS-SP7010830	10	940L			3000K			

Installation & Lifecycle

Mounting Type: Recessed

Accessories: -

Lifespan: 50,000 hours.

Warranty: 3-Years Warranty

Optional: DALI dimming, Emergency battery, White or Black reflector



